



HYDRON HVLP

PRODUCT DESCRIPTION:

HYDRON HVLP hydraulic oil is a high viscosity index antiwear hydraulic oil designed with a high viscosity index and low pour point for wider temperature range applications. It offers exceptional wear protection for hydraulic pumps and motors, alongside excellent oxidation resistance and thermal stability at high temperatures to reduce deposit formation and extend service life. Additionally, it safeguards hydraulic system components from rust and corrosion.

APPLICATION:

The HYDRON HVLP hydraulic oil is suitable for both mobile and static hydraulic applications in various industrial equipment, including hydraulic cranes, lifts, loaders, forklifts, excavators, dumpers, loading ramps, and tailboards. It may also be recommended for the hydraulic systems of metalworking machines or the circulation systems of industrial machinery.

FEATURES & BENEFITS:

- Excellent demulsibility
- Very good corrosion protection to steel
- Good corrosion protection to copper
- High ageing stability / high oxidation stability
- Good AW wear protection
- Very good hydrolytic stability
- Excellent filtration behavior (dry, wet)
- Low foaming
- Excellent air release

PERFORMANCE LEVELS: Meets or Exceeds:

- DIN 51524 Part 3, Type HVLP

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	TORQUE HVLP						
Grade			15	22	32	46	68	100	150
Kinematic Viscosity @ 104°F /40°C	ASTM D7042	cSt	15	22	32	46	68	100	150
Kinematic Viscosity @ 212°F /100°C	ASTM D7042	cSt	TBR	TBR	TBR	TBR	TBR	TBR	TBR
Viscosity Index	ASTM D2270	-	140	140	140	140	140	140	140
Density@15°C/ 60°F	ASTM D4052	g/cm ³	TBR	TBR	TBR	TBR	TBR	TBR	TBR
Flash Point (min)	ASTM D92	°C	180	200	200	200	200	200	200
Pour Point (max)	ASTM D97	°C	-33	-33	-33	-33	-33	-33	-33

DISCLAIMER:

The test data provided is not a final specification; rather, it serves as a guideline and may vary within acceptable production tolerances. Bravoil reserves the right to modify this test data. Any updates will supersede previous versions, so please refer to the most recent Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.