



GREASES

BRAVOIL™

Technical Data Sheet

ELPRIMO L 100-EP-SYN

PRODUCT DESCRIPTION:

ELPRIMO L 100-EP-Syn grease is a synthetic oil-based grease that utilizes lithium soap as its thickener technology. It is specially formulated to offer exceptional lubrication performance, particularly at low temperatures as low as -50°C, as well as under extremely high speeds. The incorporation of a low-viscosity oil, such as polyalphaolefin (PAO), further enhances its lubricating properties. This makes ELPRIMO L 100-EP-Syn grease an ideal choice for applications where low-temperature operation and high-speed performance are critical factors.

APPLICATIONS:

ELPRIMO L 100-EP-Syn grease is highly recommended for automotive applications that involve operating at both high and low temperatures. It is particularly well-suited for use in disc brake wheel bearings, balls, and steering joints. The synthetic formulation of the grease provides excellent lubrication and protection, ensuring smooth operation and reduced wear in these critical automotive components.

PRODUCT ADVANTAGES

- The operating temperature range is from -50°C to 110°C
- Low friction torque
- Quiet running
- Good oxidation stability
- Good water resistance

TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE	
NLGI Grade	-	2	3
Thickener Type	-	Lithium	Lithium
Appearance	Visual	Smooth & Homogenous	Smooth & Homogenous
Color	Visual	Off-white	Off-white
Work Penetration @25°C,	ASTM D217	265-295	220-250
Copper Strip Corrosion 24hrs @100°C	ASTM D4048	1b.	1b.
Dropping Point °C, Min	ASTM D2265	190	190
Water Washout Resistance %Wt. @79°C	ASTM D1264	max 10	max 10
Four Ball Weld Load, Kg, Min	ASTM D2596	min 250	min 250
Oil Separation %, 30hrs @100°C	ASTM D6184	max 5	max 5
Operating Temperature Range, °C	INTERNAL	-50 to 110	
Base Oil Viscosity @40°C (Cst)	ASTM D445	100	100

DISCLAIMER:

The test data provided is not a final specification; rather, it serves as a guideline and may vary within acceptable production tolerances. Bravoil reserves the right to modify this test data. Any updates will supersede previous versions, so please refer to the most recent Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.