



ELPRIMO L 100-M3

PRODUCT DESCRIPTION:

ELPRIMO L 100-M3 grease is formulated with a lithium 12-hydroxy stearate soap base and high-quality mineral base oil. It is fortified with antioxidants, rust, and corrosion inhibitors, as well as extreme pressure and anti-wear additives. The inclusion of 3% molybdenum disulfide provides additional protection against wear and shock loads. This grease is designed to offer enhanced lubrication and extended equipment life, making it an excellent choice for applications that require extra protection against wear and demanding operating conditions.

APPLICATIONS:

ELPRIMO L 100-M3 grease is a versatile, multi-purpose grease that is well-suited for various applications. It can be used for lubrication points on a variety of heavy equipment, including dozers, scrapers, earthmovers, cranes, shovels, rollers, combines, and cotton pickers. The grease is compatible with different types of antifriction bearing arrangements, from plain sleeve types to rolling element bearings, as well as bushings and other sliding surfaces or pivot points. This makes it a convenient choice for maintaining and protecting a wide range of machinery.

PRODUCT ADVANTAGES

- The operating temperature range is from -20°C to 120°C
- The presence of moly provides additional protection against wear
- Excellent load-carrying capacity
- Good resistance against water
- Good mechanical stability
- Good corrosion protection

TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE	
NLGI Grade	-	2	3
Thickener Type	-	Lithium 12-Hydroxystearate	Lithium 12-Hydroxystearate
Appearance	Visual	Smooth & Homogenous	Smooth & Homogenous
Color	Visual	Dark gray	Dark gray
Work Penetration @25°C,	ASTM D217	265-295	220-250
Copper Strip Corrosion 24hrs @100°C	ASTM D4048	1b max.	1b max.
Dropping Point °C, Min	ASTM D2265	180	180
Water Washout Resistance %Wt. @79°C	ASTM D1264	max 10	max 10
Four Ball, Load Wear Scar, Mm	ASTM D2266	0.6	0.6
Four Ball Weld Load, Kg, Min	ASTM D2596	200	200
Dry Lubricant	-	Molybdenum Disulfide	Molybdenum Disulfide
Operating Temperature Range, °C	INTERNAL	-20 to 120	
Base Oil Viscosity @40°C (Cst)	ASTM D445	90 - 110	90-110

DISCLAIMER:

The test data provided is not a final specification; rather, it serves as a guideline and may vary within acceptable production tolerances. Bravoil reserves the right to modify this test data. Any updates will supersede previous versions, so please refer to the most recent Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.