



## ELPRIMO MOLD RELEASE AGENT DEMOULDING OIL FOR CEMENT PRODUCTS

### PRODUCT DESCRIPTION:

ELPRIMO Mold Release Agent is a specialized demoulding oil designed for cement products that forms a protective barrier between the concrete and the mould surface, preventing adhesion. This layer is critical in the demoulding process as it helps to facilitate the formation of soap at the interface.

### APPLICATION:

ELPRIMO Mold Release Agent is a versatile demoulding oil that is commonly used for various applications such as tiles, cement slates, fence posts, thin flat sections, and other prefabricated elements of medium to higher quality. Its properties make it suitable for achieving optimal results in these specific uses.

### FEATURES & BENEFITS:

- Superior quality of the surface
- Light colour
- Enriched with special additives
- Prevents sticking
- Extremely handy to apply

### TYPICAL PROPERTIES:

PARAMETERS	METHOD	UNIT	TYPICAL
Appearance	Visual	-	Bright and Clear
Density, 15 °C	D 4052	g/ml	TBR
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	2.0
Flash Point, COC	D 92	°C	84
tv Test, Proc. A and B, 24 h	D 665	-	pass

### DISCLAIMER:

The test data provided is not a final specification; rather, it serves as a guideline and may vary within acceptable production tolerances. Bravoil reserves the right to modify this test data. Any updates will supersede previous versions, so please refer to the most recent Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.bravoil.ae](http://www.bravoil.ae)

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.bravoil.ae](http://www.bravoil.ae)

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.