



## GREASES

# BRAVOIL™

### Technical Data Sheet

## ELPRIMO PU 100

#### PRODUCT DESCRIPTION:

ELPRIMO PU 100 is a versatile and high-performance grease designed for extreme conditions. It has been specifically developed to offer exceptional lubrication in applications with highly loaded ball, roller, and plain bearings, particularly in high-temperature environments. This grease is ideal for industries such as paper, steel, aluminum, and chemical manufacturing, where extended service life and reliable performance are crucial requirements.

#### APPLICATIONS

ELPRIMO PU 100 grease NLGI-2 is also recommended for paper, steel, aluminum, chemical, and other industries.

#### PRODUCT ADVANTAGES

- The operating temperature range is -10°C to 150°C
- Outstanding high-temperature oxidation stability
- Reduced grease consumption at high temperatures
- Protects bearings against wear under conditions of shock loading
- Resists water washing and rusting
- Long operational life

#### TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE
NLGI Grade	ASTM D217	2
Thickener Type	-	Di- Urea
Base Oil Type	-	Mineral
Appearance	Visual	Smooth & Homogenous
Color	Visual	Light Brown
Work Penetration, 0.1 mm	ASTM D217	265-295
Dropping Point, °C, Min	ASTM D2265	>250
Cu Corrosion	ASTM D4048	1b
Oxidation Stability, Drop In Pressure, Psi	ASTM D942	max 5
Heat Stability, % Wt.	ASTM D6184	3 max
Operating Temperature Range °C	INTERNAL	-10 to 150
Base Oil Viscosity @40°C (Cst)	ASTM D445	100

#### DISCLAIMER:

The test data provided is not a final specification; rather, it serves as a guideline and may vary within acceptable production tolerances. Bravoil reserves the right to modify this test data. Any updates will supersede previous versions, so please refer to the most recent Technical Data Sheet (TDS).

#### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.bravoil.ae](http://www.bravoil.ae)

#### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.bravoil.ae](http://www.bravoil.ae)

#### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

#### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.