



GREASES

BRAVOIL™

Technical Data Sheet

ELPRIMO PU 460

PRODUCT DESCRIPTION:

ELPRIMO PU 460 is an extreme-pressure grease designed to give enhanced lubrication in loaded low to medium-speed industrial bearings, especially in continuous steel casting lines. It is also recommended for the lubrication of high-temperature slow-moving concast bearings in the steel industry. It can also be used in high-temperature, slow-moving bearing applications.

APPLICATIONS

ELPRIMO PU 460 grease NLGI 1.5 is designed to give enhanced lubrication in loaded low to medium-speed industrial bearings, especially in continuous steel casting lines. It is also recommended for the lubrication of high-temperature, slow-moving concast bearings in the steel industry.

PRODUCT ADVANTAGES

- The operating temperature range is -10°C to +150°C
- Outstanding high-temperature oxidation stability
- Good anti-corrosion properties
- Excellent resistance against water washout
- Long operational life

TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE
NLGI Grade	ASTM D217	1.5
Thickener Type	-	Di- Urea
Base Oil Type	-	Mineral
Appearance	Visual	Smooth & Homogenous
Color	Visual	Light Brown
Work Penetration, 0.1 mm	ASTM D217	305
Dropping Point, °C, Min	ASTM D2265	250
Cu Corrosion	ASTM D4048	1b
Four Ball Weld Load, Kgf, Min	ASTM D2596	250
Emcor Rust Test, Rating	IP 220	0-0
Heat Stability, %Wt.	ASTM D6184	3 max
Operating Temperature Range °C	INTERNAL	-10 to 150
Base Oil Viscosity @40°C (Cst)	ASTM D445	460

DISCLAIMER:

The test data provided is not a final specification; rather, it serves as a guideline and may vary within acceptable production tolerances. Bravoil reserves the right to modify this test data. Any updates will supersede previous versions, so please refer to the most recent Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.