



MOTO 2T

2 STROKE ENGINE OIL

PRODUCT DESCRIPTION:

Moto 2T is a high-performance lubricant specifically designed for two-stroke engines found in motorcycles, scooters, and mopeds. It is compatible with lead-free fuels and combines top-quality base stocks with advanced additives. This product is suitable for use in oil-injected systems as well as engines that require premixed gasoline/oil lubrication. Its enhanced performance offers protection against exhaust emissions and the buildup of engine carbon deposits, ensuring a cleaner and more efficient operation of the engine.

APPLICATIONS:

Moto 2T oil is specifically formulated for two-stroke air-cooled engines and can be used in various applications, including motorcycles, scooters, mopeds, snowmobiles, lawnmowers, golf carts, and chainsaws, among others. It meets the requirements of API TC lubricants. The oil should be used according to the original equipment manufacturer's recommended fuel/oil mix ratio. If the specific ratio is not provided, the general guideline is to use a 50:1 fuel/oil mix ratio.

FEATURES & BENEFITS:

- Provides piston scuffing protection and reduces smoke
- Thermal and oxidation stability
- Specially formulated to avoid spark plug fouling
- Perfectly adapted to unleaded fuel
- Protection against pre-ignition problems

PERFORMANCE LEVEL: Meets or Exceeds:

- API TC
- JASO FD
- ISO EGD

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	MOTO 2T
Kinematic Viscosity @ 104°F /40°C	ASTM D7042	cSt	TBR
Kinematic Viscosity @ 212°F /100°C	ASTM D7042	cSt	9
Viscosity Index (min)	ASTM D2270	-	120
Density @15°C/ 60°F	ASTM D4052	g/cm ³	TBR
Flash Point (min)	ASTM D92	°C	220
Pour Point (max)	ASTM D97	°C	-24
Color	Visual	-	Blue

DISCLAIMER:

The test data provided is not a final specification; rather, it serves as a guideline and may vary within acceptable production tolerances. Bravoil reserves the right to modify this test data. Any updates will supersede previous versions, so please refer to the most recent Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.