



REX L-EP

PRODUCT DESCRIPTION:

REX L-EP is a high-quality multi-purpose grease that is designed to provide extreme pressure protection. It is formulated with a lithium 12-Hydroxystearate soap thickener and high-quality mineral base oils. This grease is fortified with antioxidants, rust, and corrosion inhibitors, as well as extreme pressure and anti-wear additives. REX L-EP grease offers excellent mechanical stability, high load-carrying capacity, and effective protection against wear and corrosion. It is a reliable and versatile option for various applications where extreme pressure conditions are encountered.

APPLICATIONS

NLGI 0 and 1 greases are ideal for centralized lubrication systems due to their consistency. They are specifically recommended for steel mill lubrication, heavy-duty plain and rolling element bearings, and gearboxes that require semi-fluid grease. These greases are suitable for industrial applications with high unit pressures or shock loads. REX L-EP is also suitable for commercial vehicle and construction equipment applications such as chassis joints and pin bushing lubrication. NLGI 3 grade is recommended for inclined and vertical shaft applications, even under severe vibrations.

PRODUCT ADVANTAGES

- The operating temperature range is from -25°C to 130 °C.
- Excellent mechanical stability
- Easy to pump at low temperatures
- Excellent resistance against water
- Very good anti-wear protection
- Very good rust and corrosion protection

TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE					
NLGI Grade	-	000	00	0	1	2	3
Thickener Type	-	Lithium					
Appearance	Visual	Smooth & Homogenous					
Color	Visual	Yellow to Brown					
Work Penetration @25°C	ASTM D217	445 - 475	400-430	355-385	310-340	265-295	220-250
Copper Strip Corrosion, 24hrs @100°C	ASTM D4048	1b max.	1b max.	1b max.	1b max.	1b max.	1b max.
Dropping Point °C, Min	ASTM D2265	N/A	N/A	N/A	190	190	190
Water Washout Resistance %Wt. @79°C	ASTM D1264	N/A	N/A	N/A	Max 10		
Four Ball Weld Load, Kg, Min	ASTM D2596	200					
Operating Temperature Range, °C	INTERNAL	-25 to 130					
Base Oil Viscosity @40°C (Cst)	ASTM D445	90 -110					

DISCLAIMER:

The test data provided is not a final specification; rather, it serves as a guideline and may vary within acceptable production tolerances. Bravoil reserves the right to modify this test data. Any updates will supersede previous versions, so please refer to the most recent Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.