



REX LT

PRODUCT DESCRIPTION:

REX LT is a water-resistant calcium-soap thickened lubricating grease of NLGI 2 and NLGI 3 consistency. This is a good quality grease with excellent water resistance and good protection against corrosion.

APPLICATIONS

REX LT grease is well-suited for a variety of applications including the lubrication of nipples, spring leaves, chain drives, water pumps, non-bearing axles, and open and semi-open gear systems. Its water-resistant properties and corrosion protection make it an effective choice for these types of equipment and systems.

PRODUCT ADVANTAGES

- The operating temperature range is from -10°C to 60°C
- Very good lubricity
- Very good rust and corrosion protection
- Lower cost
- Excellent water washout properties

TYPICAL PROPERTIES:

| PARAMETERS | TEST METHODS | TYPICAL VALUE | | |
|--------------------------------|--------------|---------------------|-----------|-----------|
| | | 1 | 2 | 3 |
| NLGI Grade | - | | | |
| Thickener Type | - | Calcium Soap | | |
| Appearance | Visual | Smooth & Homogenous | | |
| Color | Visual | Yellow | | |
| Work Penetration @25°C | ASTM D217 | 310 - 340 | 265 - 295 | 220 - 250 |
| Dropping Point °C, Min | ASTM D566 | 90 | 90 | 90 |
| Operating Temperature Range °C | INTERNAL | -10 to 60 | | |
| Base Oil Viscosity @40°C (Cst) | ASTM D445 | 30 - 40 | | |

DISCLAIMER:

The test data provided is not a final specification; rather, it serves as a guideline and may vary within acceptable production tolerances. Bravoil reserves the right to modify this test data. Any updates will supersede previous versions, so please refer to the most recent Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.