



## S ULTRA 3000 MINERAL

### PRODUCT DESCRIPTION:

S ULTRA 3000 is a versatile engine oil suitable for use in passenger cars, light trucks, and farm equipment, making it ideal for applications where a single type of oil is preferred. This oil is designed to combat the formation of acids, oxidation, and foaming, offering excellent engine protection. Formulated with high-quality mineral base stock and an advanced additive system, S ULTRA 3000 ensures optimal performance and longevity for a variety of vehicles and equipment.

### APPLICATION:

This engine oil is suitable for use in a wide range of applications, including passenger cars, farm and construction equipment, stationary diesel engines, and four-stroke engines. It is designed to provide effective lubrication and protection for both gasoline and light-duty diesel engines found in these various types of equipment.

### FEATURES & BENEFITS:

- Superior viscosity retention
- Oxidation resistant
- Wear and friction protection
- Engine Cleanliness and low combustion residue
- Excellent detergency and dispersancy

### PERFORMANCE LEVELS: Meets or Exceeds:

- API Service Category SF/CD
- MIL-L-2104A

### TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	S ULTRA 3000				
Grade			40	50	15W-40	20W-50	20W-60
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	TBR	TBR	TBR	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	14.5	19.5	15.2	19.5	25.7
Viscosity Index (min)	D2270	-	95	95	135	120	120
Density @15°C/ 60°F	D4052	g/cm <sup>3</sup>	TBR	TBR	TBR	TBR	TBR
Flash Point (min)	D92	°C	220	220	220	220	220
Pour Point (max)	D97	°C	-9	-9	-33	-24	-24

### DISCLAIMER:

The test data provided is not a final specification; rather, it serves as a guideline and may vary within acceptable production tolerances. Bravoil reserves the right to modify this test data. Any updates will supersede previous versions, so please refer to the most recent Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.bravoil.ae](http://www.bravoil.ae)

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.bravoil.ae](http://www.bravoil.ae)

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.