

**PCMO****BRAVOIL™****Technical Data Sheet****S ULTRA 5000
MINERAL****PRODUCT DESCRIPTION:**

S ULTRA 5000 mineral engine oil is a high-quality multi-grade oil specifically designed to provide superior engine protection. Formulated with highly refined base stocks and premium additive technology, this oil helps prevent the accumulation of dirt and sludge in older engines. It is suitable for use in all driving conditions, whether on highways or in the city, ensuring optimal performance and longevity for a variety of vehicles.

APPLICATION:

This engine oil can be comfortably used in a mixed fleet of vehicles and equipment that have gasoline and light-duty diesel engines. It is suitable for passenger cars, farm and construction equipment, stationary diesel engines, and four-stroke engines. Its versatile formulation allows for reliable performance and protection across different types of vehicles and applications.

FEATURES & BENEFITS:

- Superior viscosity retention
- Oxidation resistant
- Wear and friction protection
- Engine Cleanliness and low combustion residue
- Excellent detergency and dispersancy
- Protection against rubber parts
- Good TBN Retention

PERFORMANCE LEVELS: Meets or Exceeds:

- API Service Category SG/CF

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	S ULTRA 5000			
Grade			15W-40	20W-50	20W-60	50
Kinematic Viscosity @ 104°F / 40°C	D7042	cSt	TBR	TBR	TBR	TBR
Kinematic Viscosity @ 212°F / 100°C	D7042	cSt	15.0	19.6	25.5	19.5
Viscosity Index (min)	D2270	-	135	120	120	95
Density @ 15°C / 60°F	D4052	g/cm ³	TBR	TBR	TBR	TBR
Flash Point (min)	D92	°C	220	220	220	220
Pour Point (max)	D97	°C	-33	-24	-24	-9

DISCLAIMER:

The test data provided is not a final specification; rather, it serves as a guideline and may vary within acceptable production tolerances. Bravoil reserves the right to modify this test data. Any updates will supersede previous versions, so please refer to the most recent Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.