

РСМО



Technical Data Sheet

S ULTRA 7000

PRODUCT DESCRIPTION:

S ULTRA 7000 mineral engine oil is a high-quality multi-grade oil that offers excellent engine protection and prevents the accumulation of dirt and sludge. It is formulated with highly refined base stocks and premium additive technology. This oil is particularly suitable for older engines operating in various driving conditions, both on highways and in the city, ensuring optimal performance and reducing the risk of engine issues caused by build-up and deposits.

APPLICATION:

Suitable for gasoline/diesel/CNG/LNG engines.

FEATURES & BENEFITS:

- · Superior viscosity retention
- Oxidation resistant
- · Wear and friction protection
- · Engine Cleanliness and low combustion residue
- Excellent detergency and dispersancy
- · Easy start at low temperatures
- · Excellent protection against sludge and varnish deposits

PERFORMANCE LEVELS: Meets or Exceeds:

API Service Category SJ/CF

TYPICAL PROPERTIES:

| PARAMETERS | TEST METHOD | UNIT | S ULTRA 7000 (MINERAL) | | | | |
|-----------------------------|-------------|-------|------------------------|-------|-------|------|------|
| SAE Grade | | | 15W40 | 20W50 | 20W60 | 50 | 40 |
| Kinematic Viscosity @ 40°C | ASTM D7042 | cSt | TBR | TBR | TBR | TBR | TBR |
| Kinematic Viscosity @ 100°C | ASTM D7042 | cSt | 15.2 | 19.6 | 25.5 | 19.5 | 15.3 |
| Viscosity Index (min) | ASTM D2270 | - | 135 | 120 | 120 | 95 | 95 |
| Density @15°C/60°F | ASTM D4052 | g/cm³ | TBR | TBR | TBR | TBR | TBR |
| Flash Point (min) | ASTM D92 | °C | 220 | 220 | 220 | 220 | 220 |
| Pour Point (max) | ASTM D97 | °C | -33 | -24 | -24 | -9 | -9 |

DISCLAIMER:

The test data provided is not a final specification; rather, it serves as a guideline and may vary within acceptable production tolerances. Bravoil reserves the right to modify this test data. Any updates will supersede previous versions, so please refer to the most recent Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60° C, exposed to hot sun or freezing conditions.