

**PCMO****BRAVOIL™****Technical Data Sheet****S ULTRA 9000
FULLY SYNTHETIC****PRODUCT DESCRIPTION:**

S ULTRA 9000 fully synthetic motor oil is developed with advanced additives technology, actively working to maintain engine cleanliness. This innovative formulation enables the oil to offer superior levels of cleansing and protection. Specifically designed for turbo-compressed, multi-valve, and direct-injection engines, this oil is an excellent choice for vehicles with advanced engine technologies. It is suitable for use in challenging conditions like motorway driving and heavy urban traffic throughout the year, ensuring optimal performance and longevity for the engine.

APPLICATIONS:

S ULTRA 9000 is highly recommended for use in both naturally aspirated and turbo-charged gasoline engines found in passenger cars, as well as light commercial vehicles. It is also suitable for four-stroke gasoline engines and portable power equipment. This versatile motor oil provides excellent lubrication and protection for these engines, ensuring optimal performance and durability in a variety of applications.

FEATURES & BENEFITS:

- Superior wear and corrosion protection.
- Protects against start-up wear in cold conditions through excellent low-temperature fluidity.
- Maintains power and economy by minimizing wear.
- Superior viscosity retention.
- Oxidation resistant.
- Engine Cleanliness and low combustion residue.

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	0W-30	0W-40	5W-20	5W-30	5W-40
API	SL/CF	SL/CF	SL/CF	SL/CF	SL/CF
ACEA	A3/B3	A3/B3	A5/B5	A3/B3	A3/B3
MB	-	229.3, 226.5	-	-	229.3, 226.5
RENAULT	RN0700	RN 0700/0710	-	RN0700	RN 0700/0710
VW	501.01 / 505	501.01 / 505	-	501.01 / 505	501.01 / 505

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	S ULTRA 9000				
SAE Grades			0W-30	0W-40	5W-20	5W-30	5W-40
Kinematic Viscosity @ 104°F /40°C	D445	cSt	TBR	TBR	TBR	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D445	cSt	10.2	14.9	8.8	10.1	15
Viscosity Index (min)	D2270	-	160	170	150	160	160
Density @15°C/ 60°F	D4052	g/cm ³	TBR	TBR	TBR	TBR	TBR
Flash Point (min)	D92	°C	220	220	220	220	220
Pour Point (max)	D97	°C	-39	-39	-39	-39	-39

DISCLAIMER:

The test data provided is not a final specification; rather, it serves as a guideline and may vary within acceptable production tolerances. Bravoil reserves the right to modify this test data. Any updates will supersede previous versions, so please refer to the most recent Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.