

# РСМО



# Technical Data Sheet

# **S ULTRA 9000**

#### MINERAL

# PRODUCT DESCRIPTION:

S ULTRA 9000 is a high-quality mineral oil designed for use in both gasoline and diesel engines, making it versatile for various driving conditions. It is especially suitable for turbo-charged engines and works well in vehicles equipped with catalysts and running on unleaded fuel.

## APPLICATIONS:

Recommended for a wide range of applications, S ULTRA 9000 is suitable for naturally aspirated and turbo-charged gasoline engines found in passenger cars, light commercial vehicles, four-stroke gasoline engines, and even portable power equipment. It is designed to deliver optimal performance and protection across these various applications.

#### **FEATURES & BENEFITS:**

- · High Viscosity Index (min)
- Excellent viscosity stability
- · Excellent detergency and dispersancy

- · Very high antiwear and anticorrosion properties
- · Very good antioxidant, antirust, antifoaming properties

## PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	15W-40	20W-50	20W-60	25W-60
API	SL/CF	SL/CF	SL/CF	SL/CF
ACEA	A3/B3	A3/B3	A3/B3	A3/B3
RENAULT	RN0700/ RN0710	RN 0700/0710	-	-
VW	501.01 / 505	501.01 / 505	501.01 / 505	-

#### TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	S ULTRA 9000			
SAE Grades			15W-40	20W-50	20W-60	25W-60
Kinematic Viscosity @ 104°F /40°C	D445	cSt	TBR	TBR	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D445	cSt	15	20.2	24.2	24.0
Viscosity Index (min)	D2270	-	142	131	145	124
Density @15°C/60°F	D4052	g/cm³	TBR	TBR	TBR	TBR
Flash Point (min)	D92	°C	220	220	220	220
Pour Point (max)	D97	°C	-33	-24	-24	-21

### DISCLAIMER:

The test data provided is not a final specification; rather, it serves as a guideline and may vary within acceptable production tolerances. Bravoil reserves the right to modify this test data. Any updates will supersede previous versions, so please refer to the most recent Technical Data Sheet (TDS).

# **HEALTH & SAFETY, ENVIRONMENT:**

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

### **HEALTH & SAFETY:**

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

# PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above  $60^{\circ}$ C, exposed to hot sun or freezing conditions.

inquiry@bravoil.ae bravoil.ae \_\_\_\_\_\_ Version: 01-2023