



S ULTRA 9000

SEMI SYNTHETIC

PRODUCT DESCRIPTION:

S ULTRA 9000 semi-synthetic motor oil stands out thanks to its advanced additive technology, providing superior levels of cleansing and protection for engines. This multigrade lubricant is designed to meet the toughest conditions, whether its heavy urban traffic, motorway driving, or any other challenging situation, all year round.

APPLICATION:

Specifically formulated for modern, high-performance gasoline and diesel engines in passenger cars, minibuses, and light trucks, S ULTRA 9000 meets the performance requirements of API SL/CF. This motor oil is designed to provide optimal lubrication and protect these engines during rigorous driving conditions, ensuring their smooth operation and long-lasting performance.

FEATURES & BENEFITS:

- Superior wear and corrosion protection
- Protects against start-up wear in cold conditions through excellent low-temperature fluidity
- Maintains power and economy by minimizing wear
- Superior viscosity retention
- Oxidation resistant
- Engine Cleanliness and low combustion residue

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	10W-30	10W-40	10W-60
API	SL/CF	SL/CF	SL/CF
ACEA	A3/B3	A3/B3	A3/B3
MB	-	229.3	-
RENAULT	RN0700/ RN0710	RN 0700/0710	-
VW	501.01 / 505	501.01 / 505	501.01 / 505

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	S ULTRA 9000		
			10W-30	10W-40	10W-60
SAE Grades					
Kinematic Viscosity @ 104°F / 40°C	D445	cSt	TBR	TBR	TBR
Kinematic Viscosity @ 212°F / 100°C	D445	cSt	11.8	15	24
Viscosity Index (min)	D2270	-	145	145	145
Density @ 15°C / 60°F	D4052	g/cm ³	TBR	TBR	TBR
Flash Point (min)	D92	°C	220	220	220
Pour Point (max)	D97	°C	-36	-36	-36

DISCLAIMER:

The test data provided is not a final specification; rather, it serves as a guideline and may vary within acceptable production tolerances. Bravoil reserves the right to modify this test data. Any updates will supersede previous versions, so please refer to the most recent Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.