



## S ULTRA FE FULLY SYNTHETIC

### PRODUCT DESCRIPTION:

S Ultra FE is a top-notch fully synthetic engine oil that offers excellent fuel efficiency and is designed to prolong the life of various types and ages of vehicles. It provides enhanced protection across a wide range of temperatures, ensuring superior engine performance and durability.

### APPLICATION:

S Ultra FE 5W-20 is a specialized fuel economy engine oil that caters to the requirements of specific OEMs such as FORD, JAGUAR, LAND ROVER, CHRYSLER, and JEEP. It is ideal for both gasoline and diesel engines that demand a 5W-20 viscosity grade fuel economy lubricant and comply with ACEA A5/B5 and ACEA A1/B1 standards. This oil is also compatible with catalytic converters.

S Ultra FE 0W-30 is a versatile, fuel-efficient engine oil suitable for gasoline and diesel passenger cars, particularly those equipped with turbochargers. It is recommended for full synthetic all-season motor oils.

S Ultra FE 5W-30 is designed for use in various gasoline and diesel automobiles, light trucks, and vans that require low viscosity (HTHS >2.9) motor oil, provided that the viscosity and quality requirements are met.

### FEATURES & BENEFITS:

- Improved fuel economy
- Superior oil film strength under all engine operating conditions.
- Enhanced engine cleanliness and sludge prevention
- Enhanced cold start-up performance
- Enhanced wear protection
- Superior protection for exhaust catalyst and diesel particulate filter.

### PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	5W-20	0W-30	5W-30
API	SN/CF	SL/CF	SL/CF
ACEA	A5/B5-16	A5/B5-16	A5/B5-16
FORD	WSS-M2C925-B	-	WSS-M2C913-D
JAGUAR LAND ROVER	STJLR.03.5004	-	STJLR.03.5003
MB	-	229.6	229.6
RENAULT	-	RN0700	RN0700
VOLVO	-	VCC 95200377	-

### TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	S ULTRA FE		
Grade			0W-30	5W-20	5W-30
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	TBR	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	10.2	8.0	10.2
Viscosity Index (min)	D2270	-	160	150	160
Density @15°C/ 60°F	D4052	g/cm <sup>3</sup>	TBR	TBR	TBR
Flash Point (min)	D92	°C	220	220	220
Pour Point (max)	D97	°C	-39	-39	-39

### DISCLAIMER:

The test data provided is not a final specification; rather, it serves as a guideline and may vary within acceptable production tolerances. Bravoil reserves the right to modify this test data. Any updates will supersede previous versions, so please refer to the most recent Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.bravoil.ae](http://www.bravoil.ae)

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.bravoil.ae](http://www.bravoil.ae)

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.