

**PCMO****BRAVOIL™****Technical Data Sheet****S ULTRA PAO**
FULLY SYNTHETIC**PRODUCT DESCRIPTION:**

S Ultra PAO is a high-quality lubricant that is formulated with PAO (Polyalphaolefin) base stocks to provide exceptional engine protection in modern cars equipped with gasoline and diesel engines, whether they are naturally aspirated or turbocharged, and with indirect or direct injection systems. It meets the latest industry standards for "Full SAPS" passenger car lubricants and surpasses the performance of conventional oils. These oils are designed to offer enhanced resistance to oxidation, superior deposit protection, improved wear protection, and excellent performance at low temperatures throughout the life of the oil.

APPLICATION:

This lubricant is suitable for use with all types of fuels, including leaded or unleaded gasoline, ethanol, LPG, diesel, and biofuels. It is also compatible with catalytic converters.

FEATURES & BENEFITS:

- Quick cold weather starting and fast protection helps extend engine life
- Outstanding thermal and oxidation stability
- Used for all high-performance gasoline engine cars equipped with direct-injection, multi-valve, and turbo-charged technologies.
- Formulated for optimum viscosity control

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	0W-30	0W-40
API	SL/CF	SN/CF
ACEA	A3/B4	A3/B4
VOLVO	95200356	-
Porsche	-	A40
MB	226.5	226.5
	229.3	229.3
	229.5	229.5
RENAULT	RN0700	RN0700
	RN0710	RN0710
VW	502 00	502 00
	505 00	505 00
BMW	LL-01	LL-01
PSA	-	-
Ford	-	WSS-M2C-937-A

TYPICAL SPECIFICATION:

PARAMETERS	ASTM	UNIT	S ULTRA PAO	
Grade			0W-30	0W-40
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	11.8	14.5
Viscosity Index (min)	D2270	-	160	170
Density @15°C/ 60°F	D4052	g/cm ³	TBR	TBR
Flash Point (min)	D92	°C	220	220
Pour Point (max)	D97	°C	-39	-39

DISCLAIMER:

The test data provided is not a final specification; rather, it serves as a guideline and may vary within acceptable production tolerances. Bravoil reserves the right to modify this test data. Any updates will supersede previous versions, so please refer to the most recent Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.