



S ULTRA PLUS SYNTHETIC

PRODUCT DESCRIPTION:

S Ultra Plus is a high-quality fully synthetic engine oil that offers exceptional engine protection for modern cars equipped with gasoline and diesel engines, whether they are naturally aspirated or turbo-charged, and whether they use indirect or direct injection. It meets the latest industry standards for passenger car lubricants with "Full SAPS" and performs better than traditional oils. This advanced oil provides improved resistance to oxidation, better protection against deposits, superior wear protection, and excellent performance in low temperatures throughout its lifespan.

APPLICATION:

This product is suitable for all types of fuel, including leaded or unleaded gasoline, ethanol, LPG, diesel, and biofuels. It is also compatible with catalytic converters.

FEATURES & BENEFITS:

- Quick cold weather starting and fast protection helps extend engine life.
- Outstanding thermal and oxidation stability.
- Used for all high-performance gasoline engine cars equipped with direct-injection, multi-valve, and turbo-charged technologies.
- Formulated for optimum viscosity control.

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	0W-20	0W-30	0W-40	5W-20	5W-30	5W-40
API	SN	SL/CF	SN/CF	SN	SN*/SL/CF	SN/CF
ACEA	A5/B5	A3/B4	A3/B4	A5/B5	A3/B4	A3/B4
VOLVO	-	95200356	-	-	-	-
Porsche	-	-	A40	-	-	A40
MB	-	226.5 229.3 229.5	226.5 229.3 229.5	-	226.5 229.3 229.5	226.5 229.3 229.5
RENAULT	-	RN0700 RN0710	RN0700 RN0710	-	RN0700 RN0710	RN0700 RN0710
VW	-	502 00 505 00	502 00 505 00	-	502 00 505 00	502 00 505 00
BMW	-	LL-01	LL-01		LL-01	LL-01
PSA	-	-	-	-	-	B71 2296
Ford	-	-	WSS-M2C-937-A	WSS-M2C-925-B	-	-
LANDROVER	-	-		STJLR.03.5004	-	-



PCMO

BRAVOIL™

Technical Data Sheet

TYPICAL SPECIFICATION:

PARAMETERS	ASTM	UNIT	S ULTRA PLUS							
Grade			0W-20	0W-30	0W-40	5W-20	5W-30	5W-40	5W-50	10W-40
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	TBR	TBR	TBR	TBR	TBR	TBR	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	8.9	11.8	14.9	8.8	11.6	15	19.5	15.0
Viscosity Index (min)	D2270	-	150	160	170	150	160	160	165	140
Density @15°C/ 60°F	D4052	g/cm³	TBR	TBR	TBR	TBR	TBR	TBR	TBR	TBR
Flash Point (min)	D92	°C	220	220	220	220	220	220	220	220
Pour Point (max)	D97	°C	-39	-39	-39	-39	-39	-39	-39	-39

DISCLAIMER:

The test data provided is not a final specification; rather, it serves as a guideline and may vary within acceptable production tolerances. Bravoil reserves the right to modify this test data. Any updates will supersede previous versions, so please refer to the most recent Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.