

AUTOMOTIVE COOLANT / ANTIFREEZE

Technical Data Sheet



PRODUCT DESCRIPTION:

SUBZERO 6277M is an extended-life coolant specifically formulated for automotive engines. It is based on ethylene glycol and is designed to meet the GM 6277M specification, which is General Motors' new extended-life coolant standard.

APPLICATION:

SUBZERO 6277M is a highly recommended extended-life coolant for both diesel and gasoline applications that require a nitrite, silicate, and phosphate-free formula. This coolant is specially formulated to meet the requirements of diesel and gasoline engines while providing excellent extended-life cooling performance.

FEATURES & BENEFITS:

- Outstanding corrosion protection
- · Contains no amines, nitrites or phosphates
- · Universal application at passenger cars and commercial vehicles.
- · Anti-cavitation, preventing foam and the retention of air, ensuring the good performance of the pump.
- · Prevents the buildup of deposits, keeping the cooling system clean.
- Long life service product

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- GM 6277M/1825M/1899M
- US FED A-A-870-A
- CHRYSLER MS 9769

- FORD WSS-M97B44-D2
- VAG G-12
- ASTM D4656

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	SUBZERO 6277M
PH	D1278	cSt	8.1
Freezing Point	D1177	°C	-37
Boiling Point	D1120	cSt	110
Density @15.5C	D4052	g/cm3	TBR

DISCLAIMER:

The test data provided is not a final specification; rather, it serves as a guideline and may vary within acceptable production tolerances. Bravoil reserves the right to modify this test data. Any updates will supersede previous versions, so please refer to the most recent Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.



BR AVOI