

**SUBZERO FL22****EXTENDED LIFE COOLANT/ ANTIFREEZE****PRODUCT DESCRIPTION:**

SUBZERO FL22 is a pre-diluted coolant that is ready to use without the need for additional water. It is ethylene-glycol-based and does not contain amines and silicates. This time-tested coolant is formulated with proven inhibitors to provide extended-life radiator antifreeze capabilities.

APPLICATION:

SUBZERO FL22 is a prediluted coolant designed to provide frost and rust protection for automotive engines. It can be used year-round to ensure optimum engine performance and protection against freezing temperatures and corrosion.

FEATURES & BENEFITS:

- Outstanding corrosion protection
- Contains no amines, nitrites or phosphates
- Universal application at passenger cars and commercial vehicles.
- Anti-cavitation, preventing foam and the retention of air, ensuring the good performance of the pump.
- Prevents the buildup of deposits, keeping the cooling system clean.
- Long life service product

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- GM 08CLAG01050 Honda E Coolant
- Ford VC-10-A2
- Hyundai 00232-19010
- Hyundai 07100-00200
- Hyundai 07100-00400 • Hyundai Long Life Coolant
- Mazda 000077508E20
- Mazda C100CL005A4X
- Mazda C122CL005A4X
- Mazda FL22 Coolant
- Nissan Anti-freeze Coolant (L250)
- Nissan KE90299934
- Nissan KE90299944
- Subaru Coolant 16218
- Suzuki Longlife Coolant
- WSS-M97B55

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	SUBZERO FL22
pH	D1278	cSt	8
Freezing Point	D1177	°C	-40
Boiling Point	D1120	cSt	110
Density @15.5C	D4052	g/cm3	TBR

DISCLAIMER:

This test data provided is not a final specification; rather, it serves as a guideline and may vary within acceptable production tolerances. Bravoil reserves the right to modify this test data. Any updates will supersede previous versions, so please refer to the most recent Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.