



AUTOMATIC TRANSMISSION FLUID

BRAVOIL™

Technical Data Sheet

SYNTHPOWER PLUS

HIGH-PERFORMANCE ATF WITH REDUCED VISCOSITY FOR BETTER FUEL EFFICIENCY.

PRODUCT DESCRIPTION:

Synthpower Plus is a cutting-edge automatic transmission fluid (ATF) that offers enhanced performance due to its low viscosity and advanced additives. It is formulated using a unique blend of HC synthetic oils and fully synthetic poly-alpha-olefins (PAO), making it suitable for use in contemporary 6/8/9-speed automatic transmissions found in SUVs, mid-size, and luxury vehicles.

APPLICATION:

Synthpower Plus is designed to meet the unique needs of modern 6/8/9-speed automatic transmissions found in high-performance SUVs and luxury vehicles. With a specific friction coefficient level, it enables the smooth transmission of high torques, allowing for quick and sporty shifting without sacrificing comfort. Additionally, its exceptional friction coefficient stability ensures consistent shifting performance throughout its entire lifespan.

FEATURES & BENEFITS:

- Adapted friction coefficient behavior for spontaneous and sporty shifting operations
- Prevention of friction vibrations in a reliable manner, thus providing maximum comfort
- Excellent friction coefficient stability over the entire service interval
- Reduced viscosity for better fuel efficiency
- Excellent shifting characteristics at low temperatures
- The best wear protection properties for reliable operation and the longest service life
- Highest oxidation and ageing stability due to a special base oil composition made of HC synthetic and fully synthetic PAO base oils
- Minimal tendency to foam
- Reliable protection against corrosion, wear, sludge accumulation and adhesion
- Neutral behavior towards gasket materials
- Miscible and compatible with other ATF of the same specification. However, in order to exploit the full product benefits of HIGHTEC ATF 9008, a complete oil change is strongly recommended.

PERFORMANCE LEVELS: Meets or Exceeds:

- Chrysler 68157995AA
- BMW 83 22 2 152 426/83 22 2 305 397 (BMW L12108)/83
- 22 2 289 720 (ATF3+)
- Fiat 9.55550-AV5
- Honda ATF-Type 3.1
- Jaguar 02JDE 26444
- Land Rover LR023288
- VW G 060 162/G 055 540
- ZF S671 090 312

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	SYNTHPOWER PLUS
Kinematic Viscosity @ 104°F /40°C	ASTM D7042	cSt	TBR
Kinematic Viscosity @ 212°F /100°C	ASTM D7042	cSt	7.25
Viscosity Index (min)	ASTM D2270	-	140
Density @15°C/ 60°F	ASTM D4052	g/cm ³	TBR
Flash Point (min)	ASTM D92	°C	200
Pour Point (max)	ASTM D97	°C	-42

DISCLAIMER:

The test data provided is not a final specification; rather, it serves as a guideline and may vary within acceptable production tolerances. Bravoil reserves the right to modify this test data. Any updates will supersede previous versions, so please refer to the most recent Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.