



SYNTO TRUCK PREMIUM MINERAL

PRODUCT DESCRIPTION:

SYNTO TRUCK PREMIUM is a high-performance diesel engine oil that provides excellent lubrication to diesel engines. It maximizes performance in the latest US, European, and Japanese heavy-duty diesel engines including severe applications such as high loads and multi-trailer applications. It exhibits outstanding detergent, dispersant, and anti-wear properties to keep the engine clean and enable efficient control of soot, sludge, and piston deposits.

APPLICATION:

Recommended for modern heavy-duty engines, a wide range of turbo-charged and naturally aspirated diesel engines as well as all kinds of gasoline engines, all types of generators, trucks, construction machinery, passenger cars, or mixed fleets comprising diesel and gasoline.

FEATURES & BENEFITS:

- High thermal and oxidation stability
- Reduced sludge buildUp, deposits and viscosity increase
- Stay-in-grade shear stability
- Excellent low temperature properties
- Wear protection and viscosity control
- Improved viscosity control and oil pumpability

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- API CI-4/SL
- ACEA E7, A3/B3/B4
- MB 228.3/229.1
- MAN M3275-1
- Volvo VDS-3
- Deutz DQC III-10
- JASO DH1
- MACK EO-N
- Cummins CES 20076/20077/78
- Global DHD1
- Renault RLD2
- MTU Type 2
- Allison C4
- Caterpillar ECF 1a, ECF 2
- DDC 93K215

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	SYNTO TRUCK PREMIUM		
			15W-40	20W-40	20W-50
Grade			15W-40	20W-40	20W-50
Kinematic Viscosity @ 104°F / 40°C	D7042	cSt	TBR	TBR	TBR
Kinematic Viscosity @ 212°F / 100°C	D7042	cSt	15.3	14.5	19.6
Viscosity Index (min)	D2270	-	135	120	120
Density @ 15°C/ 60°F	D4052	g/cm ³	TBR	TBR	TBR
Flash Point (min)	D92	°C	220	220	220
Pour Point (max)	D97	°C	-33	-24	-24

DISCLAIMER:

The test data provided is not a final specification; rather, it serves as a guideline and may vary within acceptable production tolerances. Bravoil reserves the right to modify this test data. Any updates will supersede previous versions, so please refer to the most recent Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.