



## SYNTO TRUCK PREMIUM

### SEMI SYNTHETIC

#### PRODUCT DESCRIPTION:

SYNTO TRUCK PREMIUM Semi Synthetic is a heavy-duty engine oil that provides excellent lubrication in today's diesel and gasoline engines operating in severe applications. It is designed using high-performance base oils which provide excellent low-temperature fluidity, high-temperature viscosity retention, and volatility control. SYNTO TRUCK PREMIUM is engineered to provide a strong foundation for oxidation resistance, soot handling, and wear control. It provides excellent piston deposit protection and reduced sludge formation to help provide long engine life.

#### APPLICATION:

SYNTO TRUCK PREMIUM Semi Synthetic provides demonstrated protection and performance in the latest high-power heavy-duty diesel engines from Europe, the US, and Japanese manufacturers in both on-highway and off-highway applications. It is suitable for modern low-emission engines meeting Euro 2, 3, and US 2002 emission requirements.

#### FEATURES & BENEFITS:

- Increased thermal and oxidation stability
- Reduced sludge buildUp, deposits and extended engine life
- Improved corrosion protection and advanced piston deposit control
- Advanced soot handling to control viscosity increase and sludge build up
- Enhanced low temperature pumpability

#### PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- API CI-4/SL
- ACEA E7, A3/B3/B4
- MB 228.3 / 229.1
- MAN M3275-1
- Volvo VDS-3
- Deutz DQC III-10
- JASO DH1
- MACK EO-N
- Cummins CES 20076/20077/78
- Global DHD1
- Renault RLD2
- MTU Type 2
- Allison C4
- Caterpillar ECF 1a, ECF 2
- DDC 93K215

#### TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	SYNTO TRUCK PREMIUM	
Grade			10W-30	10W-40
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	11.7	15.1
Viscosity Index (min)	D2270	-	145	145
Density @ 15°C/ 60°F	D4052	g/cm <sup>3</sup>	TBR	TBR
Flash Point (min)	D92	°C	220	220
Pour Point (max)	D97	°C	-36	-36

#### DISCLAIMER:

The test data provided is not a final specification; rather, it serves as a guideline and may vary within acceptable production tolerances. Bravoil reserves the right to modify this test data. Any updates will supersede previous versions, so please refer to the most recent Technical Data Sheet (TDS).

#### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.bravoil.ae](http://www.bravoil.ae)

#### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.bravoil.ae](http://www.bravoil.ae)

#### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

#### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.