



## OUTBOARD ENGINE OIL

# BRAVOIL™

### Technical Data Sheet

## WAVE SNOW 2T

### 2-STROKE ENGINE LUBRICANT FOR SNOWMOBILE

#### PRODUCT DESCRIPTION:

WAVE SNOW 2T is a highly advanced fully synthetic oil, specifically designed for 2-stroke engines in snowmobiles. This oil is formulated with carefully selected esters, providing effective detergency and dispersancy properties. Its synthetic base fluids ensure excellent low-temperature fluidity, while still maintaining exceptional lubricating properties even at high operating temperatures. WAVE SNOW 2T is engineered to protect and perform optimally under all operating conditions, making it a reliable choice for snowmobile engines.

#### APPLICATIONS:

WAVE SNOW 2T is recommended for use in 2-stroke engines with either injector systems or those lubricated by premix. It is versatile enough to be suitable for both racing applications and regular driving that demands high performance. It is important to follow the fuel/oil mix ratio recommended by the original equipment manufacturer (OEM). If the specific ratio is not provided, the general recommendation is to use a 50:1 fuel/oil mix ratio.

#### FEATURES & BENEFITS:

- Low ash formulation prevents deposits on pistons and ports.
- Mixes instantaneously with gasoline and remains stable.
- Excellent cold flow and lubricating properties at extreme temperatures.
- Reduces friction and wear to increase engine life

#### PERFORMANCE LEVELS: Meets or Exceeds:

- API TC
- ISO L-EGD
- JASO FD

#### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	WAVE SNOW 2T
Kinematic Viscosity @ 212°F/100°C	ASTM D7042	cSt	7.5
Kinematic Viscosity @ 104°F/40°C	ASTM D7042	cSt	41.4
Viscosity Index (min)	ASTM D2270	-	150
FLASH POINT	ASTM D92	°C	152
POUR POINT	ASTM D97	°C	-45
SPECIFIC GRAVITY	ASTM D4052	g/cm3	TBR

#### DISCLAIMER:

The test data provided is not a final specification; rather, it serves as a guideline and may vary within acceptable production tolerances. Bravoil reserves the right to modify this test data. Any updates will supersede previous versions, so please refer to the most recent Technical Data Sheet (TDS).

#### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.bravoil.ae](http://www.bravoil.ae)

#### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.bravoil.ae](http://www.bravoil.ae)

#### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

#### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.