

## РСМО



### Technical Data Sheet

# S ULTRA FULLY SYNTHETIC

#### PRODUCT DESCRIPTION:

S ULTRA is an advanced fully synthetic engine oil designed to help deliver outstanding engine protection in recent cars fitted with Gasoline and Diesel engines, naturally aspirated or turbo-charged, indirect or direct injection. It meets the requirements of the latest industry standards for "Full SAPS" passenger car lubricants and outperforms conventional oils. These oils are designed to provide improved oxidation resistance, improved deposit protection, better wear protection, and excellent low temperature performance over the life of the oil

#### APPLICATION:

Suitable for all type of fuels: Gasoline, Ethanol, LPG, Diesel and biofuels.

## **FEATURES & BENEFITS**

- · Quick cold weather starting and fast protection helps extend engine life.
- Outstanding thermal and oxidation stability.
- · Used for all high-performance gasoline engine cars equipped with direct-injection, multi-vave, and turbo-charged technologies.
- Formulated for optimum viscosity control.
- VW Standard 502 00 /505 00 (SAE 5W-40).
- Porsche Oil Category A40 (SAE 5W-40).

## PERFORMANCE LEVELS: Meets or Exceeds:

- API SN/CF
- ACEA A3/B4 PORSCHE A40

- MB 229.5
- VW 502 00 505 00
   BMW LL-01

#### TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	S ULTRA
Grade			5W-40
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	TBR
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	15
Viscosity Index (min)	D2270	-	160
Density @15°C/60°F	D4052	g/cm3	TBR
Flash Point (min)	D92	°C	220
Pour Point (max)	D97	°C	-39

#### DISCLAIMER:

The test data provided is not a final specification; rather, it serves as a guideline and may vary within acceptable production tolerances. Bravoil reserves the right to modify this test data. Any updates will supersede previous versions, so please refer to the most recent Technical Data Sheet (TDS).

## **HEALTH & SAFETY, ENVIRONMENT:**

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

#### **HEALTH & SAFETY**

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

## PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

#### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

inquiry@bravoil.ae bravoil.ae Version: 01-2023