



## S ULTRA C2-C3

### FULLY SYNTHETIC

#### PRODUCT DESCRIPTION:

S Ultra oil are advanced fully synthetic engine oil designed to help deliver outstanding engine protection. This oil meets the requirements of "Mid SAPS" passenger car lubricants with 0.08% phosphorus and 0.8% sulphated ash levels. These products are designed to provide improved oxidation resistance, improved deposit protection, better wear protection, enhanced fuel economy and excellent low temperature performance over the life of the oil.

#### APPLICATION:

Suitable for gasoline fueled automobiles requiring ACEA C2 or ACEA C3 and API SN Plus class engine oils in select SAE viscosity grades.

#### FEATURES & BENEFITS

- Outstanding wear protection under a wide variety of operating conditions.
- Special cleaning additive to help prevent the formation of sludge and harmful deposits.
- Optimal engine operating temperature, owing to thermal control formula.
- Limits formation of deposits on the most loaded engine parts.
- Provides safe operation of catalytic exhaust convertors.
- Resistant to extreme thermal load, due to high quality of base oil.
- Enables fast and easy start in extreme temperature conditions.

#### PERFORMANCE LEVELS: Meets or Exceeds:

- API SN Plus
- ACEA C2/C3
- GM Dexos 2
- MB 229.51
- VW 505 01
- BMW LL-04

#### TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	S ULTRA C2/C3
Grade			5W-30
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	TBR
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	11.5
Viscosity Index (min)	D2270	-	160
Density @15°C/ 60°F	D4052	g/cm3	TBR
Flash Point (min)	D92	°C	220
Pour Point (max)	D97	°C	-39

#### DISCLAIMER:

The test data provided is not a final specification; rather, it serves as a guideline and may vary within acceptable production tolerances. Bravoil reserves the right to modify this test data. Any updates will supersede previous versions, so please refer to the most recent Technical Data Sheet (TDS).

#### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.bravoil.ae](http://www.bravoil.ae)

#### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.bravoil.ae](http://www.bravoil.ae)

#### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

#### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.