

ENGINE CARE & FUEL ADDITIVES

Technical Data Sheet



ENGINE FLUSH

PRODUCT DESCRIPTION:

Engine Flush aids in restoring fuel efficiency, enhancing engine performance, and lowering emissions in both gasoline and diesel engines. Its powerful detergent-based formula effectively removes sludge and deposits, helping to minimize oil consumption. Safe for engine components, it can be conveniently disposed of alongside waste oil.

FEATURES & BENEFITS:

- · Helps loosen sticky valves and rings, minimizing blow-by and reducing emissions
- · Promotes lower operating temperatures through sludge removal
- Helps guite lifter noise
- Does not attack common sealing materials
- · Highly economical

APPLICATIONS:

Engine Flush is designed to clean and flush the oil circuits in gasoline and diesel engines. Its application depends on the level of oil circuit contamination. Note: it is not suitable for use in motorcycles with wet clutches.

DIRECTIONS:

A 300 ml can of Engine Flush is sufficient for up to 6 liters of oil. Add the product to warm motor oil before performing an oil change. Let the engine idle for approximately 10 minutes after adding the flush, then proceed with changing the oil and filter. Engine Flush is compatible with all commercially available motor oils.

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	ENGINE FLUSH
Kinematic Viscosity @ 104°F /40°C	ASTM D445	cSt	<7
Density@15°C/ 60°F	ASTM D4052	g/cm ³	0.80
Flash Point (min)	ASTM D93	°C	60
Pour Point (max)	ASTM D97	°C	-45
Odor			Charcteristic

DISCLAIMER:

The test data provided is not a final specification; rather, it serves as a guideline and may vary within acceptable production tolerances. Bravoil reserves the right to modify this test data. Any updates will supersede previous versions, so please refer to the most recent Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.bravoil.ae

HEAITH & SAFETY

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.bravoil.ae

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

